

Apollo - Neon Flex 06×12mm - 30m (100ft)

Powered from one end



Silicone Extruded: This product is integrally extruded from foodgrade pure silicone. UV resistant, anti-aging, IP67 waterproof, durable for long-term outdoor use. Safer silicone material will not be self-ignited even burned with fire.

Bending Direction: When its luminous surface is facing up or down, the bending direction is horizontal.

55 mm Cut Marks: It can be cut every 50mm (1.97inch) with clear cut marks on its side position.

Power Supply: Max 10mt/33ft powered from one end.






Dimmable: The neon flex can be dimmed by Triac, 1-10V, DALI or DMX system. Please use appropriate 24VDC constant voltage drivers and controllers for dimming.

Warranty: 2 Years.

Colors Available

Warm White: 2700K, 3000K	Neutral White: 4000K, 5000K	Cool White: 6000K, 6500K *	Single Color *
--------------------------	-----------------------------	----------------------------	---

Technical Specifications

Led Number / Meter	120pcs SMD2835	
Power / Meter	6W	
Lumen Flux@ 3000K	300 ~ 350Lm / meters	
CRI	>85+	
SDCM	<3	
Input Voltage	24V DC	
Cut Length	41.66 mm	
Dimension	6×12 mm	
Available Length	30 Meters, 100 feet (one side power)	
Top Shape	Flat	
View Angle	180 Deg / 270 Deg	
Bending Radius	100 mm	
Weights/Meter	100 g	
Lifespan	50,000hrs	
IP Rate	IP67	
Storage Temp.	-40°C ~ +70°C	
Top Shape	-25°C ~ +50°C	



Accessories

End cap	Caps-end-10X10
Side lead-out	Caps-wire-10X10
Aluminum clip 3cm	NF1010CL
Aluminum track 1m long	NF1010-AT-R (Round Top)
Aluminum track 1m long	NF1010-AT-F (Flat top)
5mt reel	NF1010SS-F
5mt reel	NF1010SS-R
Bendable stainless steel track	

Product Codes

5000K NF1010-30M24CV6W50KR NF1010-30M24CV6W50KF
4000K NF1010-30M24CV6W40KR NF1010-30M24CV6W40KF
3000K NF1010-30M24CV6W30KR NF1010-30M24CV6W30KF
2700K NF1010-30M24CV6W30KR NF1010-30M24CV6W27KF
R-ROUND TOP/F-FLAT TOP