# Enclosures and mounting boxes: Flush mounting box 3M black

**V71303.AU**

Enclosures and mounting boxes / Flush mounting boxes / For masonry walls

**Flush mounting box 3M black**

3-module flush mounting box, (Glow Wire 960 °C), for masonry walls, black

- Plenty of space of internal wiring
- Wide range of accessories available: anti-mortar covers, coupling joints to create multiple series of boxes
- Knockouts designed for the insertion of pipes with various cross-sections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing

**Product Status**

3 - Active

**Minimum order quantity**

15 NR

## You may also be interested in

V71303 - Flush mounting box 3M light blue



V71633 - Flat cover 3M

V71323 - Antimortar cover for flush-mount box 3M

V71563 - Joint plate for flush-mount bixes yellow

## Drawings



Space view




Backside view



3D View

## Technical data

- **Class group**: Connection devices
- **Class**: Box/housing for built-in mounting in the wall/ceiling
- **Mounting method**: Flush mounted (plaster)
- **Shape**: Rectangular
- **Construction type**: Device connection box (round/square)
- **Model**: Other
- **Provided with revolving ring**: No
- **Connectable**: Yes
- **Equipped with**: None
- **Diameter**: 0 mm
- **Length**: 59,00 mm
- **Width**: 96,00 mm
- **Depth**: 0,00 - 49,80 mm
- **Internal depth**: 50,00 mm
- **For number of electric fittings**: 3
- **Mounting switching equipment**: Screwing
- **With screws**: No
- **Housing feed-through by break-out opening**: Yes
- **Housing feed-through by seal membrane**: No
- **Housing feed-through by nozzle**: No
- **Housing feed-through by step membrane**: No
- **For tube diameter**: 20/25 mm
- **Pipe locking**: No
- **Pipe locking optional**: No
- **Inlet from the rear**: Yes
- **Number of inlets**: 12
- **Number of included spouts**: 0
- **Material**: Plastic
- **Halogen free**: Yes
- **Surface protection**: Untreated
- **Colour**: Black
- **Degree of protection (IP)**: IP00
- **Cover model**: None
- **Transparent cover**: No
- **Cover attachment**: Screwed
- **Sealable**: No
- **Circuit integrity**: None
- **With screening**: No
- **Air tight**: No
- **Max. conductor cross section**: 0
- **Number of poles of the clamp**: 0
- **Clamp position fixed**: No
- **Luminaire hook mounting**: No
- **Nozzle**: None
- **With nail lugs**: No
- **Special application**: None

## Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy (download)
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert (download)

## Packaging




**Code** 8007352080720
**Quantity** 1 NR
**Dim.** 10.6x7.4x5 [cm]
**Weight** 35.73 [g]




**Code** 8007352119437
**Quantity** 15 NR
**Dim.** 10.6x7.4x75 [cm]
**Weight** 544.95 [g]

**Code** 8007352119468
**Quantity** 300 NR
**Dim.** 59x39x44 [cm]
**Weight** 11,892 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.