

Industrial LCD Touch Display

IND-10T

10.4" Panel Mount Touch Monitor



Specification

Input Interface :

- VGA : 1 x VGA D-Sub 15 pin
- DVI : 1 x DVI-D
- HDMI : 1 x HDMI (for optional)
- Video : S-Video, Composite (optional)
- USB : 1 x USB for touch
- Power Input : 1 x DC input (terminal block)

Power Specification:

- Power Adapter : N/A
- Consumption : 20W typical, normal operation
- Power Input : 9~36V DC Input
- Power Cord : N/A

OSD :

- OSD Input : 5-key OSD buttons
- OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings, LED On/Off settings in OSD menu

Panel Specification :

- Size/ Type : 10.4" LCD
- Active Area (mm) : 211.2 (H) x 158.4 (V)
- Pixel Pitch (mm) : 0.264(H) x 0.264(V)
- Resolution : 1024 x 768 @ 60Hz, 75Hz
- Contrast Ratio : 1200 : 1 (typ.)
- Max. Colors : 16.2M (8 bits / color)
- Brightness : 400 nits (cd/m²)
- Viewing Angle : -88 ~ 88 (H); -88 ~ 88 (V)
- Touch : 5-wire resistive touch or P-cap touch screen (USB)

Environment Tolerance:

- Operating Temperature : 0 deg. C to 55 deg. C
- Storage Temperature : -20 deg. C to 70 deg. C

System :

- Power Input : 9~36V DC Input
- Dimming : 2~100% Dimming by knob
- IP grade : Front IP65
- Mounting type : Panel Mount /VESA Mount
- Bonding : Optical bonding between LCD panel and touch

Drawings

