









TITLE: 400-082-26-SPEC 6W spreader light, dim., warm white 2700k, 26°					
DRAWING No.: 400-082-26-SPEC				Sheet No.: 1	DRAWN BY: LSA
SCALE: 1 : 1	SIZE: A3	REV. NO.: 	TOLERANCES: DS/ISO 2768-f	REVIEWED BY: 	CREATION DATE: 11-03-2025
MATERIAL DESCRIPTION: Aluminium EN6082, Acrylic					
(20µ) Silver anodized according to EN ISO 7599 (50µ) Black anodized according to MIL-A 8625F					
This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.					







Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com





The 10° wedge can be reoriented in relationship to the base plate in 90° Intervals



TITLE: 400-082-26-SPEC 6W spreader light, dim., warm white 2700k, 26°					
DRAWING No.: 400-082-26-SPEC				Sheet No.: 2	DRAWN BY: LSA
SCALE: 1 : 1	SIZE: A3	REV. NO.: 	TOLERANCES: DS/ISO 2768-f	REVIEWED BY: 	CREATION DATE: 11-03-2025
MATERIAL DESCRIPTION: Aluminium EN6082, Acrylic					
(20µ) Silver anodized according to EN ISO 7599 (50µ) Black anodized according to MIL-A 8625F					
This Drawing, and the information within, is the property of Lopolight ApS and may not be used in any form without express permission there from. Lopolight reserves the right to change this drawing and assumes no liability for the information communicated herein. Use of dimensions and other information in this drawing is at the users own risk.					

LOPOLIGHT

Lopolight ApS
Bakkegaardsvej 513
DK-3050, Humlebaek
Denmark
www.lopolight.com

Tel:(+45) 32 48 50 30
info@lopolight.com

